


fischer (Mericon Stream Stream

The economical hammerset plug easy and quick fixing of threaded rods





fischer RODFORCE FGD Easy and quick fixing of threaded rods



Function

- When hammering-in the threaded rod, the plug expands in four directions as a result of the conical inner geometry.
- The plug is set in pre-positioned installation. This can be done in two different ways: Pre-installation of the threaded rods in the plug with both being hammered into the wall together or pre-inserting of the RODFORCE into the drill hole followed by hammering-in of the threaded rod.
- The teeth in the plug mechanically interlock securely with the metric thread of the threaded rod.
- The unique elements on the outside of the plug brace against the wall of the drill hole.

Your advantages at a glance

- The short plug length prevents reinforcement hits and guarantees a secure utilization in reinforced concrete.
- The teeth inside the plug allow standard, metric threads to be held. This saves a large assortment of stud screws.
- Installation without special tools: The only tool needed to set the plug is a hammer.
- The visible edge of the plug serves as a visual setting check and guarantees the correct setting as well as extra safety.
- Easy to check and adjust: To check the setting depth, the closed plug tip is used as a stop point. This predetermined break point also allows the threaded rod to be hammered-in deeper.

Function



In reinforced concrete




In full-masonry

Recommendation



- Suitable for the following building materials:
 Concrete
- Sand-lime solid brick
- Solid brick

fischer RODFORCE FGD The economical hammerset plug in its application with assortment and loads



Applications



Single pipe suspension



Heating and plumbing installation




Suspended ceilings



Fixing of pipe clamps



APPERERENTS		000000000000000000000000000000000000000
CEREFERENCES	, <i>686666666666666666666666666666</i>	որիաներիներիներիներիներիներիներիներին



fischer threaded rod plug RODFORCE FGD

nacher unedded fod plag nobr onoe r db									
		Nominal drill hole diameter	Min. drill hole depth at pre-positioned installation	Plug length	Min. drop-in penetra- tion	Threaded rod-Ø	Sales unit		
		do	h ₂	I	e ₁				
ltem	ArtNo.	[mm]	[mm]	[mm]	[mm]	[mm]	[pcs]		
FGD 10 M6	542106	10	40	35	33	-	50		
FGD 10 M6 TR 50	542107	10	40	35	33	M6 x 50	25		
FGD 10 M6 TR 60	542108	10	40	35	33	M6 x 60	25		
FGD 10 M6 TR 80	542109	10	40	35	33	M6 x 80	25		
FGD 12 M8	542111	12	40	35	33	-	50		
FGD 12 M8 TR 50	542112	12	40	35	33	M8 x 50	25		
FGD 12 M8 TR 60	542113	12	40	35	33	M8 x 60	25		
FGD 12 M8 TR 80	542114	12	40	35	33	M8 x 80	25		

fischer threaded rod plug RODFORCE FGD

Highest recommended loads ¹⁾ of an single anchor.

The given loads are valid for machine screws or threaded rods with the specified thread size.

Туре	FGD 10 M6	FGD 12 M8						
Thread size	[M]	M6	M8					
Recommended load in the respective building material F _{rec.} 2)								
Concrete C20/2	j [kN]	0.31	0.36					
Solid sand-lime brick KS 12	[kN]	0.31	0.36					
Solid brick MZ 12	[kN]	0.19	0.33					

1) Required safety factors are considered.

²⁾ Valid for tensile load, shear load and oblique load under any angle.

fischer FIXPERIENCE The design and information software suite



- The modular design program includes engineering software and application modules.
- The software is based on international design standards (ETAG 001 and EC2, such as EC1, EC3 and EC5), including the national application documents. All common force and measurement units are available.
- Incorrect input will be recognized and the software gives tips to get a correct result. This ensures a safe and reliable design every time.
- The graphical display can easily be rotated through 360°, panned, tilted or zoomed as required.
- The 3D display gives a detailed and realistic image.
- The "live update" feature helps to keep the program up to date ensuring you are always working with the latest version.
- Free download and updates at www.fischer.de/fixperience-en

Our service to you



We are available to you at any time as a reliable partner to offer technical support and advice:

- Our products range from chemical resin systems to steel anchors through to nylon anchors.
- Competence and innovation through own research, development and production.
- Global presence and active sales service in over 100 countries.
- Qualified technical consulting for economical and compliant fastening solutions. Also on-site at the construction site if requested.
- Training sessions, some with accreditation, at your premises or at the fischer ACADEMY.
- Design and construction software for demanding applications.

This is what fischer stands for



FIXING SYSTEMS



AUTOMOTIVE SYSTEMS



FISCHERTECHNIK



CONSULTING

See the extensive main catalogue or visit our website at www.fischer.de for information about the complete fischer range

fischer Deutschland Vertriebs GmbH Klaus-Fischer-Strasse 1 · 72178 Waldachtal Germany

Tel. 07443 12-6000 · Fax 07443 12-8297 Technical hotline 01805 202900* www.fischer.de · info@fischer.de

* 14 ct. per minute from German fixed network.

fischer Austria GmbH Wiener Strasse 95 2514 Traiskirchen Austria Tel. 02252 53730-0 · Fax 02252 53730-70 www.fischer.at · technik@fischer.at

